

2ft LED T5 — Shatter Proof Ballast Compatible

Description

LEI Ballast compatible 2ft LED T5 tube can work with most popular electronic ballasts capable of replacing your existing fluorescent T5 lamps without any additional wiring.

It provides exceptional LED lighting with reduced energy and maintenance costs. With PET+Glass structure, it can be used in special place such as food market, schools, and hospital.

Features

- Direct Replacement - works with existing fluorescent electronic ballasts
- Frosted Glass Tube - Better transparency, thermal conductivity and light evenly
- 240° light emitting area
- Shatterproof: Glass with PET coating



Specification

Type	T5
Base	Medium Bi-Pin G5
Wattage	9W
Lumens	900-1000
Input Voltage	120-277V, 347V determined by ballast
CRI	83
Beam Angle	160°
Dimmable	No
Rated Lifetime-L70	50,000 hour
Operating Temperature	-20°C - 45°C (-4° F to 113°F)
Environment	Dry, Damp
Material Usage	RoHS compliant, no mercury
Certification	NSF, UL, cULus

Ordering Information

Model No.	Product	Initial Lumens	Fluorescent Equivalent
LEIT5-HO-9W549-3000K	9W, 2FT, Ballast Compatible LED T5HO, 3000K, Shatterproof	900	24W
LEIT5-HO-9W549-4000K	9W, 2FT, Ballast Compatible LED T5HO, 4000K, Shatterproof	950	24W
LEIT5-HO-9W549-5000K	9W, 2FT, Ballast Compatible LED T5HO, 5000K, Shatterproof	1000	24W