

12.5W LED T8 – Ballast Bypass- Type B

32W Fluorescent Liner Replacement

Description

LEI T8 LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. This lamp has a particularly wide beam spread of 240 degrees and rated lifetime of 50,000 hours.


This LED T8 tube does not require a ballast to work with and offers a built-in universal line voltage driver.



Features

- By Pass Ballasts: AC 120~277V
- 240° light emitting area
- cULus classified
- 5 years warranty
- UL Sanitation certificate Shatter Proof, PET cover tube/Food Equipment, NSF-2 High Efficacy: more than 100lm/W
- No mercury and no UV

Photometric Specs



Packing Information

Case	25 pcs/case
Dimensions	124 * 21.5 * 19.5 CM (48.82 * 8.46 * 7.68 inch)
Net Weight	7.5 KGS (16.53 lbs)

Ordering Information

Model No.	Product	Initial Lumens
LEIBPT8-SP4F12.5W-30	LED T8, 12.5W, 4FT, Ballast Bypass, 3000K, Shatterproof	1650
LEIBPT8-SP4F12.5W-35	LED T8, 12.5W, 4FT, Ballast Bypass, 3500K, Shatterproof	1650
LEIBPT8-SP4F12.5W-40	LED T8, 12.5W, 4FT, Ballast Bypass, 4000K, Shatterproof	1750
LEIBPT8-SP4F12.5W-50	LED T8, 12.5W, 4FT, Ballast Bypass, 5000K, Shatterproof	1800

Specification

Type	T8
Base	G13
Power Input	Double-ended
Wattage	12.5W
Lumens	1650 / 1750 / 1800
Input Voltage	AC 120-277V, Ballast By Pass
CRI	83
Beam Angle	160°
Power Factor	0.9 nominal
Rated Lifetime-L70	50,000 hour
Operating Temperature	-20°C - 45°C (-4° F to 113°F)
Environment	Dry, Damp
Material Usage	RoHS compliant, no mercury
Certification	NSF, cULus, DLC