

18W LED T8 – Ballast Bypass - Type B

32W Fluorescent Liner Replacement

Description

LEI T8 LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. This lamp has a particularly wide beam spread of 240 degrees and rated lifetime of 50,000 hours.

This LED T8 tube does not require a ballast to work with and offers a built-in universal line voltage driver.




Features

- By Pass Ballasts: AC 120~277V
- 240° light emitting area
- cULus Classified
- 5 years warranty
- UL Sanitation certificate Shatter Proof, PET cover tube/Food Equipment, NSF-2 High Efficacy: more than 100lm/W
- No mercury and no UV

Specification

| | |
|-----------------------|-------------------------------|
| Type | T8 |
| Base | G13 |
| Power Input | Double-ended |
| Wattage | 18W |
| Input Voltage | AC 120-277V, Ballast By Pass |
| CRI | 83 |
| Beam Angle | 160° |
| Power Factor | 0.9 |
| Rated Lifetime-L70 | 50,000 hour |
| Operating Temperature | -20°C - 45°C (-4° F to 113°F) |
| Environment | Dry, Damp |
| Material Usage | RoHS compliant, no mercury |
| Certification | NSF, cULus, DLC |

Photometric Specs



Packing Information

| | |
|------------|---|
| Case | 25 pcs/case |
| Dimensions | 124 * 21.5 * 19.5 CM (48.82 * 8.46 * 7.68 inch) |
| Net Weight | 7.5 KGS (16.53 lbs) |

Ordering Information

| Model No. | Product | Initial Lumens | Case Qty |
|--------------------|---|----------------|----------|
| LEIBPT8-SP4F18W-30 | LED T8, 18W, 4FT, Ballast Bypass, 3000K, Shatterproof | 2000 | 25 |
| LEIBPT8-SP4F18W-35 | LED T8, 18W, 4FT, Ballast Bypass, 3500K, Shatterproof | 2020 | 25 |
| LEIBPT8-SP4F18W-40 | LED T8, 18W, 4FT, Ballast Bypass, 4000K, Shatterproof | 2100 | 25 |
| LEIBPT8-SP4F18W-50 | LED T8, 18W, 4FT, Ballast Bypass, 5000K, Shatterproof | 2200 | 25 |